

# CALIBRATION

## TM 6602 / TM 6612 / TM6630

### Thermometers

3 models:

TM6602: Thermocouple,

TM6612: RTD

TM6630: Thermocouple and RTD

Protected for on-site use


Metrological and control tool

- Well adapted for different process job procedures thanks to their ranges and specific functions as data recording
- High accuracy: 0,02% of reading
- Very low temperature coefficient: 10 ppm /°C in thermocouples and 7 ppm/°C in resistance even in bad outside environmental conditions accuracies are not modified
- Measurement of 14 thermocouples and 12 RTD types
- Display in °C, °F, mV and Ohms
- Data recording and onscreen exploitation


User friendly, robust, these tools have been designed to simplify temperature transmitters and probes maintenance and commissioning. They measure in thermocouple and/or RTD's.




Thermometers of series TM use a graphic display making easier programming and reading.



Function menu



Calibrated sensor menu



Reading display

# CALIBRATION

Process transmitters and other sensors are more and more reliable and accurate, therefore calibrators performances need to be at the same level. That is the reason why AOIP provides 0,02% of accuracy for thermocouples and Rtd for these onsite instruments.

The resolution is programmable, by user for better reading, upto 1mΩ or 1μV,.

## Specifications (@ 23°C±5°C and between 45% and 75% of relative humidity)

### DC VOLTAGE

Function	Range	Resolution	Accuracy / 1Yr	Range
IN	100 mV	1 μV	0,020% r + 3μV	-10 mV /100mV

Temperature coeff < 15 ppm R /°C from 0°C to 18°C and 28°C to 50 °C.

### Temperature with Thermocouples

Type	IN range	Resolution	Accuracy / 1 yr
K	- 250 to - 200°C	0,20°C	0,90°C
	- 200 to - 120°C	0,10°C	0,3°C
	- 120 to - 50°C	0,05°C	0,02 % r+ 0,12°C
	-50 to + 1 372°C	0,05°C	0,02 % r+ 0,11°C
T	- 250 to - 200°C	0,2°C	0,80°C
	- 200 to - 50°C	0,05°C	0,25°C
	- 50 to + 400°C	0,05°C	0,02 % r+ 0,09°C
J	- 210 to - 200°C	0,05°C	0,30°C
	- 200 to - 120°C	0,05°C	0,25°C
	- 120 to + 60°C	0,05°C	0,020 % r+ 0,11°C
	+ 60 to + 1 200°C	0,05°C	0,020 % r+ 0,09°C
E	- 250 to - 200°C	0,1°C	0,55°C
	- 200 to - 100°C	0,05°C	0,20C
	- 100 to + 450°C	0,05°C	0,020 % r+ 0,07°C
	+450 to + 1 000°C	0,05°C	0,020 % r+ 0,05°C
R	- 50 to + 150°C	0,50°C	0,95°C
	+ 150 to + 550°C	0,20°C	0,40°C
	+550 to + 1 768°C	0,10°C	0,020 % r+ 0,30°C
S	- 50 to + 150°C	0,5°C	0,85°C
	+ 150 to + 550°C	0,2°C	0,020 % r+ 0,4°C
	+550 to + 1 768°C	0,1°C	0,020 % r+ 0,3°C
B	+ 400 to + 900°C	0,2°C	0,95°C
	+900 to + 1 820°C	0,1°C	0,50°C
U	- 200 to - 100°C	0,05°C	0,35°C
	- 100 to + 600°C	0,05°C	0,20°C
L	- 200 to - 100°C	0,05°C	0,30°C
	- 100 to + 900°C	0,05°C	0,20°C
C	- 20 to + 900°C	0,1°C	0,30°C
	+900 to + 2 310°C	0,1°C	0,020 % r+ 0,15°C
N	- 240 to - 190°C	0,2°C	0,60°C
	- 190 to - 110°C	0,1°C	0,25°C
	- 110 to - 0°C	0,05°C	0,15°C
	+ 0 to + 1 300°C	0,05°C	0,020 % r+ 0,07°C
Platine	- 100 to + 1 400°C	0,05°C	0,3°C
Mo	0 to + 1 375°C	0,05°C	0,020 %r+ 0,10°C
NiMo/NiCo	- 50 to + 1 410°C	0,05°C	0,020 %r+ 0,35°C

CJC accuracy : ± 0,3°C

Temperature Coefficient:<20ppm/°C from 0 to 18°C and 28 to 50°C

# CALIBRATION

## RTD Specifications (@ 23°C±5°C and between 45% and 75% of relative humidity)

### Resistance

Function	Range	Resolution	Accuracy / 1yr	Range	Notes
In	400 Ohm	1 mΩ	0,012% r + 10 mΩ	0 Ω to 400 Ω	Automatic detection : 2, 3 or 4 wires.
	3600 Ohm	10 mΩ	0,012% r + 100 mΩ	0 Ω to 3600 Ω	Automatic detection : 2, 3 or 4 wires.

Temperature coefficient: <7ppm/°C from 0 to 18°C and 28 to 50°C

Sensor	Range	Resolution	Accuracy / 1yr
Pt 50 ( $\alpha = 3851$ )	- 220°C + 850°C	0,01°C	0,012 % + 0,06°C
Pt 100 ( $\alpha = 3851$ )	- 220°C + 850°C	0,01°C	0,012 % + 0,05°C
Pt 100 ( $\alpha = 3916$ )	- 200°C + 510°C	0,01°C	0,012 % + 0,05°C
Pt 100 ( $\alpha = 3926$ )	- 210°C + 850°C	0,01°C	0,012 % + 0,05°C
Pt 200 ( $\alpha = 3851$ )	- 220°C + 1 200°C	0,01°C	0,012 % + 0,12°C
Pt 500 ( $\alpha = 3851$ )	- 220°C + 1 200°C	0,01°C	0,012 % + 0,07°C
Pt 1 000 ( $\alpha = 3851$ )	- 220°C + 760°C	0,01°C	0,012 % + 0,05°C
Ni 100 ( $\alpha = 618$ )	- 60°C + 180°C	0,01°C	0,012 % + 0,03°C
Ni 120 ( $\alpha = 672$ )	- 40°C + 205°C	0,01°C	0,012 % + 0,03°C
Ni 1 000 ( $\alpha = 618$ )	- 60°C + 180°C	0,01°C	0,012 % + 0,03°C
Cu 10 ( $\alpha = 427$ )	- 70°C + 150°C	0,10°C	0,012 % + 0,18°C
Cu 50 ( $\alpha = 428$ )	- 50°C + 150°C	0,01°C	0,012 % + 0,06°C

Temperature Coefficient: < 10 % of accuracy/°C.

Accuracy is given for a 4 wires connection. Sensor accuracy is not taken into account in this accuracy.

Automatic wires number detection

Measuring current: 0.65 mA

### Measurement functions:


**Calibrated sensors:** A database can be created to design curves for sensors after calibration in relation with the corrections showed on a calibration report.

**Scaling:** This operation allows to correct probes errors. Scaling is performed using up to 10 segments, in order to fit with the real calibrated value.

**Data recording:** Data are recorded either manually on event or automatically with programmed frequency. Data are dated and can be displayed as list or curves.

Burst 'SALVE':		
Start date: --/--/---- 16:12:36		
N°	Time	°C
1	00:00:00.0	21.45
2	00:00:00.9	21.84
3	00:00:01.7	22.75
4	00:00:02.9	23.39
5	00:00:03.8	23.97
6	00:00:04.7	24.49
7	00:00:05.5	24.94

Graph ...



# CALIBRATION

## Other functions:

**Interface language:** TM have 5 languages: French, English, German, Italian and Spanish.

**Display contrast:** When dark conditions, user can modify display contrast and switch on display back-light. Back-light timer programmable

**Display resolution:** User can select 3 resolutions (upto 3 decimal places): High, middle or low resolution.

**Date and time display:** These informations are permanently display on the screen

## Statistics:

At the bottom of the screen, maximum, average and minimum values measured are displayed. Reset function allows re-calculating of the values.

**Hold:** To freeze the measuring value.

**Filter:** A filter in seconds can be applied in order to avoid fluctuation of the value.

**Embedded software update:** According to the improvements for these calibrators, AOIP offers you the upgrade of the instrument using USB port free of charge.

## Power supply

In standard TM Series are delivered with 4 AA batteries. An optional rechargeable Batteries + charger allows to use instrument directly connected to the main or with the rechargeable batteries

## Autonomy:

Mode	Measure
Autonomy	40 hours

## Mechanical characteristics and applied standards

Dimensions (Without sheath): 157x85x45 mm

Weight: 306 g

Waterproof: IP 54 acc EN 60529

Environmental conditions

Reference domain: 23°C ± 5°C, relative humidity: 45 % to 75 %.

Nominal working domain: -10°C to + 50°C, relative humidity: 20 % at 80 % w/o condensation.

Limit working domain: - 10°C to + 55°C, relative hum: 10 % to 80 % (70 % at 55°C).

Transport and storage conditions: - 30°C to + 60°C (without batteries or rechargeable batteries).

Electrical safety: EN 61010

EMC: EN61326

Thermocouples Connection with miniature compensated connector

RTD Connection 4 pin round connector or 4 banana plugs

USB Connection for PC connection (Software upgrade and application with DATA CAL)

## Supplied in standard:

Protection sheath, 4 AA batteries, instruction manual, transportation wrist-strap .

Optional external Charger + batteries connectable to the main

## Ordering instructions:

Thermocouple Thermometer	TM 6602
RTD Thermometer	TM 6612
Thermocouple and RTD Thermometer	TM 6630

## Options:

Rechargeable batteries +Charger	AN 6011
Flexible thermocouple type K	T101
Rigid thermocouple type K	T102
Teflon flexible thermocouple type K	T103
Air ambient Pt100	S101D
Waterproof Pt100	S102D



AOIP  
BP 182  
91133 Ris Orangis Cedex  
Tel: +33 169 028 900  
FRANCE  
[www.aoip.com](http://www.aoip.com)



Accréditation  
n° 2.1525  
Température



Accréditation  
n° 2.1524  
Électricité-magnétisme